

Torque Wrench



Materials	
Handle	Aluminium (TWlue)
Open-end	Chrome plated steel (Silver)

P/N	Open-end wrench size		Coupling torque		Connector Type
	mm	inch	Nm	in.ITWs	
TW060T034	6	15/64	0.34	3	SMC
TW060T045	6	15/64	0.45	4	1.0mm
TW06T056	6.4	1/4	0.56	5	SSMA
TW06T090	6.4	1/4	0.9	8	SSMA
TW08T056	8	5/16	0.56	5	SMA
TW08T090	8	5/16	0.9	8	SMA / 3.5mm / 2.92mm / 2.4mm / 1.85mm
TW08T135	8	5/16	1.35	12	SMA / 3.5mm / 2.92mm / 2.4mm / 1.85mm
TW140T056	14	0.551	0.56	5	TNC / TNCA
TW140T135	14	0.551	1.35	12	TNC / TNCA
TW14T056	14.3	9/16	0.56	5	TNC / TNCA
TW14T135	14.3	9/16	1.35	12	TNC / TNCA
TW16T056	15.9	5/8	0.56	5	TNC / TNCA
TW16T135	15.9	5/8	1.35	12	TNC / TNCA
TW19T090	19	3/4	0.9	8	N / NMD type
TW19T135	19	3/4	1.35	12	N / 7mm
TW20T090	20	25/32	0.9	8	N/ NMD type
TW20T135	20	25/32	1.35	12	N / 7mm

*Coupling torque is customizable.